

7/PRTS

09/857353

JC18 Rec'd PCT/PTO 0 4 JUN 2001

1/16

ASW  
DEC 28, 2001

## Specification

5

### Transport System for Small Components

The invention relates to a transport system for small components, in particular electrical components, which are arranged in series in said transport system.

Such a transport system is known from EP 0 085 837 B1. This known transport system consists of cassettes having a plurality of levels, with a plurality of rod-shaped magazines being received in each level and said magazines each accommodating a series of components. These magazines are movable and, for processing the components, are each removed from the cassette and inserted in the processing tool and, after processing, are received again in an output cassette. For passing an entire cassette from one processing station to the next one, the cassette is shifted to a transportation table or another means of transportation and is moved to the next processing station.

25

This system, though constituting the latest prior art for transporting small components, still involves some disadvantages. In producing a small component, the time necessary for changing the cassettes between the processing stations and for inserting the magazines into the processing tools still takes a relatively high share.

To make these times less relevant with respect to the entire production time, two processing steps per magazine carrier are carried out in a row at those process-

ing stations where this is possible. However, some processing steps, such as matching of the magnets in the production of relays, have different processing times.  
40 In case of such processing steps carried out in a row, the slower one of the two stations thus always determines the clock feed, thereby reducing again the efficiency of two processing units at a magazine carrier.

45 It is thus the object of the invention to indicate a transport system increasing the efficiency of a production line.

According to the invention, this object is met in that  
50 said transport system is designed as form chain having an arbitrary number of chain links and the small components are accommodated in the chain links.

The form chain can be passed from one processing station  
55 to to next one without a problem, whereby the insertion of cassettes in the processing stations and of the magazines in the clock modules are eliminated. The design of the transport system as form chain provides the additional advantage that differences in the clock time can  
60 be compensated by chain loops between the individual processing stations. Due to the fact that one time the first working station and another time the second working station needs a longer clock time, the chain loop arranged therebetween one time becomes shorter and one  
65 time longer, without the two working stations impeding each other.

It is expedient to provide only one accommodation cavity per chain link so that feeding always can be carried out  
70 immediately after processing, in contrast to the case with two accommodation cavities where feeding is also dependent on the processing time of the additional component.

75 The accommodation cavity preferably has a resilient wall  
through which the component is urged against an opposite  
rigid wall. Moreover, it is advantageously formed as  
through opening, permitting access to both sides of the  
component. For access to both sides, it is advantageous  
80 furthermore if the chain links are pivotable about an  
axle or pin transverse to the direction of insertion of  
the accommodation cavity. If the form chain is passed in  
horizontal direction, processing of the components can  
take place from above, and if processing from the lower  
85 side is desired, the form chain is moved in a loop such  
that the bottom side of the components is directed up-  
wardly. It has turned out as an especially space-saving  
solution to guide the chain in the processing station in  
vertical direction so that processing can take place  
90 from both sides thereof. The arrangement of the pin  
transversely to the direction of insertion of the compo-  
nents in the accommodation cavity provides the addi-  
tional advantage that the loops between the processing  
stations hang down due to gravity so that there are thus  
95 no specific measures necessary for accommodating the  
buffer loops.

However, it is just as well possible that the chain  
links are pivotable perpendicularly to the direction of  
100 accommodation of the accommodation cavity. This design  
has the advantage that the chain can be guided horizon-  
tally in a bend or a circle and thus can be fed better  
to processing stations arranged in horizontally stag-  
gered manner. This modification also is advantageous for  
105 use in small rooms or for guiding the chain through sev-  
eral rooms.

In a slightly more complex embodiment, the chain links  
are connected via two mutually perpendicular axles so  
110 that, with the exception of the increased manufacturing

costs and the more complex guiding of the chain, the advantages of the two modifications described hereinbefore are united.

115 The chain links are inexpensively made by plastics injection molding. The axles or pins between the chain links preferably consist of metal and project laterally beyond the walls of the accommodation cavity. At the projecting ends of the metal pins, the chain links on  
120 the one hand can be guided in ideal manner and on the other hand can be fixed exactly in the processing stations. Guiding and fixing on the metal pins has the advantage that no wear occurs on the plastics chain link and no formation of particles takes place which may en-  
125 tail problems in the production of electronic components.

It is expedient if the accommodation cavities at least have the height of the components to be accommodated. In  
130 this case, the component may be accommodated completely in the accommodation cavity of the form chain and the form chain, for storage or delivery, may be wound on a spool or bobbin.

135 Further embodiments and advantageous developments are indicated in the dependent claims.

The invention will be elucidated hereinafter in more detail by way of embodiments shown in the drawings in  
140 which

Fig. 1 shows a side view of a chain link according to the invention,

145 Fig. 2 shows a top plan view of the chain link according to Fig. 1,

- Fig. 3 shows a front view of the chain link according to Fig. 1,
- 150 Fig. 4 shows a top plan view of a form chain consisting of chain links according to Fig. 1,
- 155 Fig. 5 shows a side view of a chain link in which the direction of insertion of the components to be accommodated is parallel to the connecting axles of the adjacent chain link,
- 160 Fig. 6 shows a top plan view of the chain link according to Fig. 5,
- 165 Figs. 7 and 8 show a top plan view and a side view, respectively, of a chain link adapted to be connected to the adjacent chain link via two mutually perpendicular pivot axles,
- 170 Figs. 9 and 10 show a side view and a top plan view, respectively, of a connecting piece inserted between the chain links according to Figs. 7 and 8 to form a form chain,
- 175 Fig. 11 shows a top plan view of a form chain having mutually perpendicular pivot axles along with chain links according to Figs. 7 and 8 and connecting pieces according to Figs. 9 and 10,
- 180 Figs. 12 and 13 show a sectional side view and a top plan view, respectively, of a chain link having a modified pivot axle construction and component fixation,

185 Figs. 14 and 15 show a sectional side view and a top  
plan view, respectively, of a form chain  
having chain links according to Figs. 12  
and 13.

190 Figs. 1 to 4 illustrate a first embodiment of the trans-  
port system according to the invention. The transport  
system consists of a form chain 1 (cf. Fig. 4) composed  
of a series of chain links 2. Each chain link 2 has an  
accommodation cavity 3 in which one small component 4  
195 each can be accommodated and fixed. For fixing the small  
components 4, the chain link has a rigid wall 5 and a  
resilient wall 6. The resilient wall 6 consists of an  
outer wall 7 having on the inside thereof a central web  
8 extending in the direction of insertion of the small  
200 components 4 and having on both sides thereof resilient  
arms 9 extending therefrom. Between the free ends of the  
resilient arms 9 and the inside of the outer wall 7  
there is thus formed an air gap 10 into which the resil-  
ient arms 9 can retract upon accommodation of a small  
205 component 4. The resilient arms <sup>10</sup>~~10~~, on the outsides  
thereof, have a bead 11 facing in the direction of the  
accommodation cavity 3 and extending in the direction of  
insertion of the small components 4 on the resilient  
arms 9. By means of the beads 11 on the resilient arms  
210 9, the small component 4 thus is urged against the oppo-  
site rigid wall 5 and fixed. The resilient arms 9 as  
well as the beads 11 extend over the full height of the  
accommodation cavity so that the small component to be  
accommodated can be fixed at all levels. The accommoda-  
215 tion cavity 3 is designed as through opening, permitting  
access to the component from both sides thereof.

On the outside of rigid wall 5, there are arranged two  
lateral arms 12 and 13 each having a bore 14 for accom-  
220 modating a pin for connecting the chain links. On the  
opposite side of chain link 2, the outside of outer wall

7 has a central arm 16 with a bore 17 arranged thereon which, upon connection of the chain links 2, is slid between the two lateral arms 12 and 13 and is connected thereto by insertion of the common pin 15. The width of the central arm 16 is matched to the spacing between the two lateral arms 12, 13 such that the chain links still can be pivoted well about the connecting pin 15, while however axial movement between the chain links is excluded. The resilient wall 6 and the rigid wall 5 in the embodiment shown are laterally connected via the two side walls 18 and 19. These side walls 18 and 19 are spaced apart exactly in the length of the component 4 to be accommodated. Rigid wall 5, along the majority of its length, has a U-spaced recess 20, so that the component to be accommodated is urged against the lateral sections 5a and 5b of wall 5 only.

On the outside of side walls 18 and 19, there are arranged elongate projections 21 and 22 in the longitudinal direction of the chain, which serve for guiding the chain links. These projections 21 and 22 are arranged at the same level as pins 15 mutually connecting the chain links, and in the width thereof approximately correspond to the diameter of the pins 15. The pins 15 project beyond the outsides of lateral arms 12, 13 to such an extent that the face side thereof is flush with the outside of projections 21, 22.

In an embodiment not shown in the drawings, there are provided no side walls 18, 19 and rigid wall 5 as well as resilient wall 6 are connected via the projections 21, 22 only.

The exact positioning of the chain links in the tool takes place by means of pins 15 that are made of metal. In contrast thereto, the remainder of the chain links is made by inexpensive plastics injection molding. Due to

guiding and positioning on the projecting sections of  
 260 the metal pins 15, wear on the plastics body is avoided,  
 and particle formation due to wear, involving great  
 problems in the production of electronic components, is  
 eliminated.

265 Fig. 4 illustrates a form chain in a top plan view, with  
 the form chain consisting of chain links as described  
 with reference to Figs. 1 to 3. This form chain 1 is a  
 vertically deflectable form chain, i.e. the pins 15 are  
 arranged perpendicularly to the direction of insertion  
 270 of the components 4 in the accommodation cavities 3.

Figs. 5 and 6 show a side view and a top plan view, re-  
 spectively, of a chain link of a horizontal form chain.  
 The essential difference from the chain links shown in  
 275 Figs. 1 to 4 resides in that the connecting pin 15  
 (shown in Fig. 5) extends in the direction of insertion  
 of a component 4 in the accommodation cavity. The lat-  
 eral arms 12, 13 thus are arranged above each other on  
 rigid wall 5. The bore 17 in the central arm 16 arranged  
 280 on the opposite outer wall 7 also extends in the direc-  
 tion of insertion of a component in the accommodation  
 cavity 3, so that the central arm 16, upon mating of  
 chain links 2, can be received between the lateral arms  
 12, 13. In this embodiment, the pin 15 is not arranged  
 285 to be projecting beyond the lateral arms 12, 13, so that  
 fixing of the chain links 2 in the tool takes place via  
 the lateral projections 21 and 22 only. All other fea-  
 tures are analogous to the chain link described in Figs.  
 1 to 4.

290

A horizontal form chain consisting of chain links as de-  
 scribed in Figs. 5 and 6 can be bent in horizontal di-  
 rection and thus may easily be passed to processing sta-  
 tions distributed in a room.



295

Figs. 7 to 11 shows the constituent parts of a form chain 1 with two pivot axles or pins 15a and 15b as well as part of the form chain proper. All features corresponding to the form chain according to Figs. 1 to 4 bear the same reference numerals and will not be described in the following. The form chain with two pivot pins consists of chain links 2 (cf. Figs. 7 and 8) and connecting pieces 23 (cf. Figs. 9 and 10) which are inserted between the chain links 2 upon assembly of the form chain. The chain links 2 on one side thereof receive the pin 15a transversely to the direction of insertion of the small components 4 in the accommodation cavity 3 and on the opposite side thereof receive the pin 15b perpendicularly to said direction of insertion of the small components 4 in the accommodation cavity. In the embodiment shown, the lateral arms 12a and 13a on the side of rigid wall 5 are arranged so as to receive pin 15a transversely to the direction of insertion in accommodation cavity 3, whereas on the side of resilient wall 6 on outer wall 7, the lateral arms 12b and 13b are arranged above each other so that they can receive the connecting pin 15b in the direction of insertion in the accommodation cavity. The connecting piece 23 shown in Figs. 9 and 10 consists of two halves 23a and 23b that are mutually identical, but connected to each other in a manner displaced by 90°. Each of the connecting halves 23a and 23b has a bore 24a and 24b, respectively, through which the pins 15a and 15b, respectively, are introduced upon assembly of the form chain.

325

In the embodiment shown, the lateral arms 12a and 13a are spaced apart by the same distance as lateral arms 12b and 13b. Due to this, the two halves 23a and 23b of the connecting piece can be formed in identical manner and just need to be offset from each other by 90°.

330

However, it is just as well possible to space the lateral arms 12a and 13a as shown in Fig. 2 and to form the connecting piece 23a correspondingly wider.

335

Fig. 11 shows the form chain with the chain links according to Figs. 7 and 8 and the connecting piece according to Figs. 9 and 10 in the assembled state. The half 23a of the connecting piece is received between lateral arms 12a and 13a, and the other half 23b is received between lateral arms 12b and 13b of the adjacent connecting piece. By insertion of the pins 15a and 15b, the chain links are fixedly connected to each other so as to be pivotable about pins 15a and 15b, respectively.

345

The pins 15a laterally project beyond the outsides of the lateral arms 12a and 13a to such an extent that the end faces are aligned with the outside of projections 21 and 22. This form chain, which is double-deflectable, thus may also be guided via the projections 21, 22 and the pins 15a.

Figs. 12 to 15 show an additional embodiment of a vertically deflectable form chain. Features corresponding to those of the form chains described hereinbefore bear the same reference numerals and shall not be elucidated in more detail. The chain links of this form chain, on the side of rigid wall 5, are provided as well with two lateral arms 12, 13 having respective bores 14. On the opposite side, the chain link has two additional lateral arms 25, 26 which, with respect to their position, are arranged internally of the lateral arms 12, 13 and have circular axle-type projections 27 on the outside thereof which upon mating of the chain links engage the bores 14 of lateral arms 12, 13 of the adjacent chain link from the inside thereof. The end faces of lateral arms 12, 13 are each formed with a slope 28 extending inwardly. Upon mating of the chain links, the slope 28 rides onto the

365

axle-type projections 27, whereby the lateral arms 12, 13 are resiliently bent outwardly and the axle-type projections 27 may latchingly engage the bores 14. In this embodiment, the resilient wall 6 consists of two resilient arms <sup>31</sup>~~28~~ which at the lower end thereof are fixedly connected to outer wall 7 and the upper end of which urges the component 4 against the opposite rigid wall 5. The resilient arms <sup>31</sup>~~28~~, at the upper inside thereof, are provided with a bead 29 exerting pressure on the outside of the component 4.

For centering the chain link in a processing station, the outside of stationary wall 5 is formed with a slope 30 at which the centering means of the tool engages, thereby exactly determining the position of the chain link in the tool.

The invention is not restricted to the embodiments shown. For example, it is also possible to employ the resilience feature depicted in the preceding embodiments in the form chain according to Figs. 12 to 15.